

AC750 Wireless Dual Band Router

WF2710



Features:

- >802.11AC standard of next generation Wi-Fi technology
- >Workes seamlessly with all 802.11a/b/g/n/ac devices
- >2.4GHz 300Mbps & 5GHz 433Mbps simultaneous dual band
- >3 * 5dBi high gain antennas for powerful wireless coverage
- >Multiple SSID providing up to 6 additional wireless networks for visitors
- >Easy wireless security setup at a push of WPS button
- >Quick setup, with built-in multilingual web management page

Brief:

The netis router WF2710 equipped with the next generation 802.11AC Wi-Fi technology, will offer you simultaneous dual band connection with 433Mbps wireless speeds over the crystal clear 5GHz band and 300Mbps over the 2.4GHz band, ideal for faster downloading, online gaming, Internet calling and HD video streaming

www.netis-systems.com

AC750 Wireless Dual Band Router

WF2710

Specification:

Wireless	
Standards	IEEE 802.11b/g/n 2.4GHz; IEEE 802.11a/n/ac 5GHz
Signal Rate	Up to 300Mbps 2.4GHz; UP to 433Mbps 5GHz
Frequency Range	2.4-2.4835GHz; 5.180-5.825GHz
Transmit Power	20dBm (MAX)
Data Transfer Rate	802.11ac: 80MHz(433Mbps) 802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP, WDS, AP+WDS, Repeater, Client, Multiple AP
Wireless Security	64/128-bit WEP SSID Broadcast Enable/Disable WPA-PSK/WPA2-PSK (TKIP/AES) Wireless MAC Filtering
Hardware	
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1 * 10/100M Auto MDI/MDIX RJ45 WAN port; 4 * 10/100M Auto MDI/MDIX RJ45 LAN port
LED	PWR, WPS, SYS, 2.4G, 5G, LAN1-4, WAN, WPS
Button	Default, WPS
Antenna	4 * external 5dBi antennas, omni-directional
Power Supply	DC 12V/1A (Output)
Dimensions(L x W x H)	145 x 58 x 41 mm
Weight	151g
Software	
WAN Type	DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Bandwidth Control
Access Control	IP/MAC/Domain Filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, WOL, Remote Management, Firmware upgrade, Backup & Restore
Others	
Certification	FCC, CE, KC
Environment	Operating Temperature: 0°C~40°C Operating Humidity: 10%~90% non-condensing Storage Temperature: -40°C~70°C Storage Humidity: 5%~90% non-condensing
Package	1 * WF2710 1 * 12V/1A Power Adapter 1 * Ethernet Cable 1 * Quick Installation Guide

Topological Graph:

